



GRAND HARMONY SERIES SPECIFICATIONS

SPECIFICATIONS	GH22D	GH22Q
Type	5½"	5½"
Construction	Ø 140mm (5.5") steel sphere enclosure	Ø 140mm (5.5") steel sphere enclosure
Mounting depth	90mm (3 ½")	90mm (3 ½")
Drive-units	Woofers: 4"(100mm) with 1.2" (32mm) high temperature voice coil, ferrite magnet motor Tweeter: Soft dome ¾" (19mm) liquid-cooled voice coil, neodymium magnet motor	Woofers: 4"(100mm) with 1.2" (32mm) high temperature voice coil, ferrite magnet motor Tweeter: Soft dome ¾" (19mm) liquid-cooled voice coil, neodymium magnet motor
Nominal Impedance	6 ohm	6 ohm
Nominal Power Handling	80W (150W Transients)	80W (150W Transients)
Operating power	15-100W	15-100W
Crossover	2,200Hz 12dB/ octave	2,200Hz 12dB/ octave
Frequency Response	80-22,000Hz (-5dB)	80-22,000Hz (-5dB)
Frame Dimension	Ø 208mm x 2mm (8 ³ / ₈ " x 5/64")	198mm x 2mm (7 ³ / ₄ " x 5/64")
Mounting cutout	Ø 182mm	166mm x 166mm
Sensitivity (2.83V 1M)	86 dB	86 dB
Weight	1.8 kg (3.96 lbs)	1.8 kg (3.96 lbs)
Finish	White	White

* Morel operates a policy of continuous products design improvement, consequently specifications are subject to alteration without prior notice.